



SITTEN
FOR PROFESSIONALS

Compact POS SUPRA 15J100



|Client display

|VFD

|MSR

MODEL	SUPRA 15J100G	SUPRA 15J100W
Reference	POS1124	POS1125
EAN	-	-
Colour	Black	White
MAIN SYSTEM		
CPU	Intel Celeron J1900 2GHz	
Memory	4Gb DDR3 SO-DIMM 1600MHz (Maximum 8Gb)	
Storage capacity	64Gb SSD SATA (Other configurations by ordering)	
Operative system	Windows 7, Windows 8.1, POS Ready 7	
INTEGRATED DEVICES AND SENSORS		
Graphics card	Integrated Intel HD Graphics	
Audio card	Realtek ALC662-VD 5.1 CH Audio	
Printer	No	
Monitor or client display	Optional	
Magnetic Stripe Reader (MSR)	Optional	
COMMUNICATIONS		
Network card	10/100/1000 Mbps	
WiFi	Optional	
PORTS & CONNECTIONS		
Display	1 x VGA (With 12V power output)	
USB	6 (Rear 2, Back 4 / USB 2.0 x 6 Ports), USB A type 1 (Rear 1, Reserved for MSR/SCR/I-Button)	
Serial Port	COM 1 with 5V/12V power output on 9pins COM2~3 RJ-45, Full Signal COM4 RJ-11, Only TX/RX, 12V power output, Reserved for CDP COM6 RJ-45, Only TX/RX, 5V power output, Reserved for MSR	
Ethernet	1 x RJ45	
DISPLAY & GRAPHICS		
Screen	15" TFT LED Backlight	
Resolution	1024x768	
Touch Screen	Project Capacitive Touch	
Luminance	300 cd/m ² (typ.)	
OTHERS		
Dimensions (WxHxD)	POS: 364 x 333 x 210 mm Packing: 500 x 470 x 300 mm	
Weight	POS: 5,3 Kg Packing Weight: 8 Kg	
Temperature	Operation: 0°C ~ 40°C at 10% ~ 80% humidity Storage: -20°C ~ 60°C at 10% ~ 80% humidity	
Certifications	CE, FCC, KC	